

SPECIFICATION OF DDW55/27

Dimensions/ Weight		Under carriage		Wrench assembly	
Length/Width/Height	9550*2560*2700 mm	Structure	Box welded frame,	Type	Clamp jaw
Entry angle	15.5°	Travel	Self-propelled on track crawler	Max breakout torque	75000 Nm
Machine weight	17.5 ton	Travel speed	0-2.5 km/h, forward & reverse	Thread greasing	Automatic
Operator station		Track	Steel type	Pipe loader	
Cabin	Closed cabin with A/C	Track plate width	400 mm	Type	Automatic pipe loader
Rotation	0-90°	Rear stabilizer	2	Pipe box capacity	24
Control system	Electronic & hyd	Drill mast		Mud pump	
Operation controls	Joystick 2	Transmission type	Rack & pinion	Type	On board
Engine		Hose carrier	Full length of chain type	Volume	800 L/min
Make	Cummins	Setup mode	Double cylinder	Maximum pressure	8 Mpa
Rated power	194 KW	Rotary drive		Drill pipe	
Rated speed	2200 rpm	Rotary torque	27000 N.M	Type	Φ 89*4500 mm
Fuel tank capacity	220 L	Rotary speed	136 r/min	Thread	NC31
Hydraulic system		Transmission	Gear box	Tools	
Max pressure (rotary & carriage)	35 Mpa	Carriage		Back reamer	
Max pressure (control sys.)	21 Mpa	Maximum thrust/pullback force	550 KN	330, 430, 530, 630, 730, 820, 920, 1050 mm	
Hydraulic tank capacity	500 L	Max travel speed	52 m/min		
Stake down		Max travel distance	5.8 m		
Anchoring type	Hydraulic dual anchoring				
Hole nos.	2				

※ Specifications for reference only subject to change prior to notice.※

VARIETY OF USEFUL DOWN HOLE EQUIPMENT SUPPLIES



Special make drill pipe



Mud mixing & recycling



Cutting type Backreamer



Cone type Backreamer



Beacon housing & drill bit



F5 & Transmitter



Paratrack 2

DW/TXS CONSTRUCTION EQUIPMENT (BEI JING) CO., LTD.

No.6, Huoxing Fifth Street, Huo County Development Area Tongzhou District, Beijing, China.

Postal code: 101109 Tel: +86 10 80582365 Fax: +86 10 80582515 Web: www.dwtxs.cn Email: feishubing@dwtxs.com



DDW55/27

HORIZONTAL DIRECTIONAL DRILL

DW/TXS CONSTRUCTION EQUIPMENT (BEI JING) CO.,LTD.

DW*TXS*



WORLD WIDE!

DDW 55/27

DWTXS

DIVERSITY & RELIABILITY!



ROTARY AND CARRIAGE

All power transmitted by gear in the drive gear box makes the power has no lose and keeps the efficiency and rapidness of the drilling system.

POWER STATION

Cummins engine has always been site proven to be a good choice for the tough jobs of the drilling machine by the big power and maintenance free.

DRILL MAST

Heavy-duty rack-and-pinion thrust drive is field-proven to push/pull through long, tough bores.

ANCHORING SYSTEM

Heavy-duty stake down system allows you to push or pull with full machine thrust and remain secure in virtually any drilling condition.



SWIVELLING CABIN!
HIGH OPERATOR COMFORT
AND CONVENIENCE!




PULL FORCE: 55 TON
TORQUE: 27000 NM

DDW55/27

MASTER OF DRILL RIGS!



DWTXS



WRENCH SYSTEM

Open-top vise wrenches are angled toward the operator, excellent view of the tool joint when making up and breaking out pipe.

FLUID PUMP

The onboard mud pump can be adjustable for the specified requirement of bentonite fluid during your different condition of drilling work to make your project economic and safe.



PIPE LOADER

Automatic pipe loader for a easy and fast adding and change of rods on the job site make the work more continuously.



SELF-SUPPORTING!